

transmitter to cause a cellular telephone to transmit the data output from the camera memory;

a receiving station coupled to the cellular telephone transmitter by a cellular network to receive image data;

means, at the receiving station, for image processing;

means for resetting the camera memory to be reused for subsequent images once an image is transmitted to the receiving station; [and]

a return link for sending commands from the receiving station to the CPU, wherein the commands are directions for obtaining further images as needed by the means for image processing; and

an image storage device coupled to the receiving station to store images received by the receiving station.

2. (Unamended) The apparatus of claim 1, wherein the CPU interfaces to a camera memory of an existing digital still camera.

3. (Unamended) The apparatus of claim 1, wherein the cellular telephone transmitter comprises:
a standard cellular telephone; and
a cellular modem.

4. (Unamended) The apparatus of claim 1, further comprising means for packaging images as electronic mail messages prior to transmission by the cellular telephone transmitter.

5. (Unamended) The apparatus of claim 1, further comprising means for handling a serial line interface protocol connection between the cellular telephone transmitter and the receiving station.

1 N.E. 6. (Unamended) The apparatus of claim 1, further
2 comprising means for encrypting image data prior to transmission
3 by the cellular telephone transmitter.

A₂ 1 7. (Once Amended Herein) The apparatus of claim 1,
2 further comprising a means for causing the digital still camera
3 to capture images [in] on a periodic basis, wherein the CPU is
4 programmed to periodically transmit an image to free the camera
5 memory for accepting subsequent images.

1 N.E. 8. (Unamended) The apparatus of claim 1, further
2 comprising means for determining a location of the portable image
3 transfer system and means for including a location indication
4 with each image.

A₃ 1 9. (Once Amended Herein) The apparatus of claim 1,
2 [further comprising a return link for sending commands from the
3 receiving station to the CPU at the remote station] wherein the
4 commands represent user directions to be displayed at the remote
5 station directing the user to capture additional images as needed
6 by the means for image processing.

1 10. (Once Amended Herein) The apparatus of claim [9]
2 1, wherein the [remote station further comprises means for
3 sampling selected portions of an image in response to the
4 commands sent from the receiving station] commands are directions
5 directed at the remote station directing the digital still camera
6 or CPU to capture additional image data as needed by the means
7 for image processing.

1 N.E. 11. (Unamended) The apparatus of claim 1, further
2 comprising a remote printing device for printing images processed
3 by the receiving station.